



(12) **United States Patent**
Lazarus

(10) **Patent No.:** **US 9,604,033 B2**
(45) **Date of Patent:** **Mar. 28, 2017**

(54) **BODY CAVITY DRAINAGE DEVICES WITH LOCKING DEVICES AND RELATED METHODS**

(71) Applicant: **Harrison M. Lazarus**, Salt Lake City, UT (US)

(72) Inventor: **Harrison M. Lazarus**, Salt Lake City, UT (US)

(73) Assignee: **Harrison M. Lazarus**, Salt Lake City, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 307 days.

(21) Appl. No.: **14/318,550**

(22) Filed: **Jun. 27, 2014**

(65) **Prior Publication Data**
US 2015/0374959 A1 Dec. 31, 2015

(51) **Int. Cl.**
A61M 27/00 (2006.01)
A61M 25/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A61M 25/0136* (2013.01); *A61M 1/008* (2013.01); *A61M 25/007* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61M 1/008; A61M 2025/0019; A61M 2025/0081; A61M 25/007; A61M 25/0102;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,393,002 A 1/1946 Smith
2,898,917 A 8/1959 Wallace
(Continued)

FOREIGN PATENT DOCUMENTS

RU 2012371 C1 5/1994
RU 2415682 C1 4/2011
(Continued)

OTHER PUBLICATIONS

Ben-Isaac et al., "Flexible Fiberoptic Pleuroscopy: Pleural and Lung Biopsy*," *Experimental Approaches*, Chest Journal No. 67, <http://journal.publications.chestnet.org/data/Journals/CHEST/20966/573.pdf>, May 5, 1975, pp. 573-576.

(Continued)


Primary Examiner — Adam Marcetich

(74) *Attorney, Agent, or Firm* — TraskBritt

(57) **ABSTRACT**

A body cavity drainage device includes a drainage tube having a proximal end, a distal end, and one or more lumens extending longitudinally through a wall thereof. The distal end may be configured to be inserted into a body cavity of a patient during use of the body cavity drainage device. An activation apparatus is configured to alter a position of the distal end of the drainage tube relative to the proximal end of the drainage tube. The activation apparatus may include a rotatable control device and one or more flexible members disposed within the one or more lumens extending longitudinally through a wall of the drainage tube. The one or more flexible members may be operably coupled to the rotatable control device and to the drainage tube. Methods relate to forming and using a body cavity drainage device.

19 Claims, 8 Drawing Sheets



(51)	Int. Cl.		5,616,131 A	4/1997	Sauer et al.	
	<i>A61M 25/01</i>	(2006.01)	5,630,795 A	5/1997	Kuramoto et al.	
	<i>B65H 75/44</i>	(2006.01)	5,653,696 A	8/1997	Shiber et al.	
	<i>A61M 1/00</i>	(2006.01)	5,772,670 A	6/1998	Brosa	
			5,807,341 A	9/1998	Heim	
(52)	U.S. Cl.		5,895,400 A	4/1999	Abela	
	CPC	<i>A61M 25/0102</i> (2013.01); <i>A61M 25/0147</i>	5,897,534 A	4/1999	Heim et al.	
		(2013.01); <i>A61M 2025/0019</i> (2013.01); <i>A61M</i>	5,987,344 A	11/1999	West et al.	
		<i>2025/0081</i> (2013.01); <i>A61M 2207/00</i>	6,045,623 A	4/2000	Cannon et al.	
		(2013.01); <i>B65H 75/4431</i> (2013.01); <i>B65H</i>	6,171,277 B1 *	1/2001	Ponzi	A61B 18/1492
		<i>2701/36</i> (2013.01); <i>B65H 2701/537</i> (2013.01)				604/22
			6,183,450 B1	2/2001	Lois	
			6,193,691 B1	2/2001	Beardsley	
(58)	Field of Classification Search		6,254,581 B1	7/2001	Scott	
	CPC	A61M 25/0113; A61M 25/0136; A61M	6,468,260 B1 *	10/2002	Bumbalough	A61M 25/0136
		25/0147; A61M 27/00; A61M 25/0133;				600/434
		A61M 25/0105; A61M 2025/015; A61B	6,500,167 B1	12/2002	Webster	
		2034/301; A61B 2017/003; A61B	6,514,273 B1	2/2003	Voss et al.	
		2017/00318; A61B 2017/00323; A61B	6,530,913 B1	3/2003	Giba et al.	
		2017/00327; B65H 75/4431; B65H	6,530,935 B2	3/2003	Wensel et al.	
		2701/537; B65H 2701/34; B65H 2701/35;	6,638,253 B2	10/2003	Breznock	
		B65H 2701/36; B65H 2701/37; A43C	6,907,992 B2	6/2005	McMichael et al.	
		11/165; Y10T 24/2187; Y10T 74/1967;	7,037,290 B2	5/2006	Gardeski et al.	
		Y10T 403/32262; H02G 11/02; A45F	7,407,128 B1 *	8/2008	Chang	B65H 75/4431
		5/004; G01B 2003/101				242/385.4
	See application file for complete search history.		7,497,854 B2	3/2009	Gill et al.	
			7,578,814 B2	8/2009	Accisano, III et al.	
			7,740,623 B2	6/2010	Nayak et al.	
			7,758,586 B2	7/2010	Muto et al.	
			8,220,460 B2	7/2012	Tanaka	
			8,246,752 B2	8/2012	Boyle, Jr.	
			8,388,759 B2	3/2013	Boyle, Jr. et al.	
			8,409,070 B2	4/2013	Carol et al.	
			2001/0005785 A1	6/2001	Sachse	
			2001/0007922 A1	7/2001	Schwager	
			2003/0208252 A1	11/2003	O' Boyle et al.	
			2003/0225364 A1	12/2003	Kraft et al.	
			2004/0035017 A1 *	2/2004	Yang	B65H 75/4431
						33/767
			2004/0116852 A1	6/2004	Scopton	
			2005/0184186 A1 *	8/2005	Tsoi	B65H 75/4431
						242/378.1
			2005/0277875 A1	12/2005	Selkee	
			2006/0142695 A1	6/2006	Knudson	
			2006/0173449 A1	8/2006	Sharareh et al.	
			2006/0264925 A1	11/2006	Sharareh et al.	
			2006/0264988 A1	11/2006	Boyle	
			2006/0280773 A1	12/2006	Roschak et al.	
			2007/0016133 A1	1/2007	Pepper	
			2007/0060997 A1	3/2007	de Boer	
			2007/0078455 A1	4/2007	Rashidi	
			2007/0156116 A1 *	7/2007	Gonzalez	A61B 1/0052
						604/528
			2007/0167923 A1	7/2007	Deal	
			2007/0287993 A1 *	12/2007	Hinman	A61B 17/062
						606/1
			2008/0021415 A1	1/2008	Durkin et al.	
			2008/0045921 A1	2/2008	Anderson et al.	
			2008/0097293 A1	4/2008	Chin et al.	
			2008/0236209 A1 *	10/2008	Conti	E05B 45/005
						70/18
			2009/0005771 A1	1/2009	Lieber et al.	
			2009/0012365 A1 *	1/2009	Ueno	A61B 1/0052
						600/146
			2009/0062769 A1	3/2009	Graves et al.	
			2009/0227900 A1	9/2009	Kim et al.	
			2009/0270838 A1	10/2009	Berthiaume et al.	
			2009/0299327 A1	12/2009	Tilson et al.	
			2010/0101061 A1 *	4/2010	Ha	A43B 3/0042
						24/712.5
			2010/0137775 A1	6/2010	Hu et al.	
			2010/0168731 A1	7/2010	Wu et al.	
			2010/0191057 A1	7/2010	Jansen et al.	
			2010/0222664 A1	9/2010	Lemon et al.	
			2010/0249490 A1	9/2010	Farnan	
			2010/0249520 A1	9/2010	Shelton, IV et al.	
			2010/0264244 A1 *	10/2010	Spencer	B65H 75/28
						242/378
			5,540,648 A	7/1996	Yoon et al.	
			5,601,087 A	2/1997	Gunderson et al.	
(56)	References Cited					
	U.S. PATENT DOCUMENTS					
	3,225,762 A	12/1965	Guttman			
	3,416,532 A	12/1968	Grossman			
	3,610,231 A	10/1971	Takahashi et al.			
	3,683,929 A	8/1972	Holter			
	3,830,238 A	8/1974	Kurtz et al.			
	3,863,641 A	2/1975	Popa			
	3,937,418 A *	2/1976	Critelli	B65H 75/4431		
				119/796		
	3,943,929 A	3/1976	Patel			
	4,068,383 A *	1/1978	Krebs	G01B 3/1005		
				242/385.4		
	4,105,031 A	8/1978	Kurtz et al.			
	4,202,510 A *	5/1980	Stanish	B65H 75/4431		
				242/384.7		
	4,203,430 A	5/1980	Takahashi			
	4,228,802 A	10/1980	Trott et al.			
	4,439,189 A	3/1984	Sargeant et al.			
	4,571,239 A	2/1986	Heyman			
	4,608,982 A	9/1986	Pollard			
	4,692,154 A	9/1987	Singery et al.			
	4,769,019 A	9/1988	Kerwin			
	4,862,891 A	9/1989	Smith			
	4,883,474 A	11/1989	Sheridan et al.			
	4,920,980 A	5/1990	Jackowski			
	5,026,358 A	6/1991	Everett, Jr. et al.			
	5,040,543 A	8/1991	Badera et al.			
	5,047,018 A	9/1991	Gay et al.			
	5,108,368 A	4/1992	Hammerslag et al.			
	5,141,503 A	8/1992	Sewell			
	5,157,813 A *	10/1992	Carroll	A43C 7/00		
				24/68 B		
	5,205,830 A	4/1993	Dassa et al.			
	5,207,661 A	5/1993	Repschlager			
	5,297,310 A	3/1994	Cox et al.			
	5,300,050 A	4/1994	Everett, Jr. et al.			
	5,312,357 A	5/1994	Buijs et al.			
	5,364,351 A	11/1994	Heinzelman et al.			
	5,370,610 A	12/1994	Reynolds et al.			
	5,397,321 A	3/1995	Houser et al.			
	5,409,462 A	4/1995	Ross			
	5,409,468 A	4/1995	Sachse			
	5,456,664 A *	10/1995	Heinzelman	A61M 25/0147		
				600/585		
	5,540,648 A	7/1996	Yoon et al.			
	5,601,087 A	2/1997	Gunderson et al.			

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0040285 A1 2/2011 Boyle
 2011/0062268 A1* 3/2011 Cheng B65H 75/4431
 242/378.1
 2011/0077498 A1 3/2011 McDaniel
 2011/0213300 A1 9/2011 McWeeney et al.
 2011/0224647 A1 9/2011 Lazarus
 2011/0264089 A1 10/2011 Zirkle et al.
 2011/0282153 A1* 11/2011 Ueki A61B 1/0052
 600/149
 2012/0116161 A1 5/2012 Nieman et al.
 2012/0157921 A1 6/2012 Hoofnagle et al.
 2012/0172703 A1 7/2012 Esguerra et al.
 2013/0023840 A1 1/2013 Loske et al.
 2013/0046250 A1 2/2013 Bode
 2013/0158379 A1 6/2013 Selkee
 2013/0204087 A1 8/2013 Jaworek et al.
 2013/0211385 A1 8/2013 Lazarus
 2013/0276718 A1* 10/2013 Valadez A01K 27/004
 119/796
 2013/0310767 A1 11/2013 Solar et al.
 2014/0150782 A1 6/2014 Vazales et al.
 2014/0193138 A1 7/2014 Koren

2014/0290014 A1* 10/2014 Myrick A43C 11/165
 24/712.2
 2015/0148595 A1 5/2015 Bagwell et al.
 2015/0374889 A1* 12/2015 Lazarus A61B 17/3415
 604/541
 2015/0374959 A1 12/2015 Lazarus

FOREIGN PATENT DOCUMENTS

WO 9325264 A1 12/1993
 WO 9952481 A1 10/1999

OTHER PUBLICATIONS

“Catheter prevents clogging,” Research & Development, <<<http://www.rdmag.com/printpdf/award-winners/2011/08/catheter-prevents-clogging>>>, Aug. 14, 2011, 3 pages.
 “Express Dry Seal Chest Drain, Instructions for Use,” Atrium, www.atriummed.com (2003) 2 pages.
 “Medical pleuroscopy”, <<http://www.cancercenter.com/treatments/medical-pleuroscopy/>>, Cancer Treatment Centers of America, retrieved Aug. 19, 2013, 2 Pages.
 “Rocket® Cardiothoracic Range,” Rocketmedical, Issue 1, R89947, Jan. 2011, 23 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

1

BODY CAVITY DRAINAGE DEVICES WITH LOCKING DEVICES AND RELATED METHODS

BACKGROUND

Field

Embodiments of the invention relate to body cavity drainage devices and related devices and methods.

State of the Art

Drainage devices, especially for the evacuation of a pleural cavity, may consist of a hollow flexible tube inserted through an incision into the pleural cavity. The shape and configuration of the pleural cavity often necessitates multiple incisions to be made to permit the drainage tube to reach various locations in the pleural cavity. The need for multiple incisions may generally result in an extended hospital stay for a patient suffering from a severe case of pleurisy.

BRIEF SUMMARY

In one embodiment of the disclosure, a body cavity drainage device for a patient includes a drainage tube having a proximal end, a distal end, and one or more lumens extending longitudinally through a wall thereof. The distal end may be configured to be inserted into a body cavity of a patient to facilitate use of the body cavity drainage device. The body cavity drainage device may also include an activation apparatus configured to alter a position of the distal end of the drainage tube relative to the proximal end of the drainage tube. The activation apparatus may include a rotatable control device, one or more flexible members disposed within the one or more lumens extending longitudinally through a wall of the drainage tube, the one or more flexible members operably coupled to the rotatable control device at a proximal end of the one or more flexible members and to the drainage tube at or near a distal end of the one or more flexible members, and a compliant locking mechanism configured to maintain an angular position of the rotatable control device when in a locked position and in the absence of a torque applied to the rotatable control device, and to allow rotation of the control device when in an unlocked position upon application of a torque to the rotatable control device.

In another embodiment of the disclosure, a body cavity drainage device for a patient may include a drainage tube having a proximal end and a distal end and an activation apparatus coupled to the proximal end of the drainage tube. The activation apparatus may include a pinion gear attached to a control device, at least one rack meshed with the pinion gear, at least one flexible member extending along a length of the drainage tube and coupled to the distal end of the drainage tube, the at least one flexible member attached to the at least one rack, and a compliant locking mechanism proximate the control device, the compliant locking mechanism comprising a locking lever and serrations configured to engage with gear teeth of the pinion gear when the locking lever is in a locked position.

In yet another embodiment of the disclosure, a method of forming a body cavity drainage device for a patient may include coupling an activation apparatus to a proximal end of a drainage tube, the activation apparatus configured to bend the drainage tube in response to a torque input at a rotatable control device of the activation apparatus, and engaging a locking mechanism with the rotatable control

2

device to substantially prevent rotation of the rotatable control device in the absence of an applied torque to the rotatable control device.

In yet another embodiment of the disclosure, a method of draining fluid from a body cavity, comprising positioning a distal end of a tube of a body cavity drainage device at a first position within the body cavity, draining fluid from the body cavity through the distal end of the tube of the body cavity drainage device in the first position, depressing a locking lever to unlock a rotatable control device of the body cavity drainage device external to the body cavity, and moving the distal end of the tube of the body cavity drainage device to a second, different position within the body cavity. Moving the distal end of the tube of the body cavity drainage device to a second, different position within the body cavity may include rotating the rotatable control device of the body cavity drainage device, the rotatable control device coupled to the distal end of the tube of the body cavity drainage device by flexible members.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 shows a top view of a drainage device according to an embodiment of the present disclosure;

FIG. 2 shows a side view of the drainage device of FIG. 1;

FIG. 3 shows a top cross-sectional view of the drainage device of FIG. 1;

FIG. 4 shows a top cross-sectional view of the drainage device of FIG. 1 in a bent position;

FIG. 5 shows an enlarged top view of an activation apparatus according to an embodiment of the present disclosure;

FIG. 6 shows a side cross-sectional view of the activation apparatus of FIG. 5;

FIG. 7 shows a schematic side view of a drainage device according to an embodiment of the present disclosure;

FIG. 8 shows a side view of a drainage tube placement tool according to an embodiment of the present disclosure;

FIG. 9 shows a detail view of the drainage tube placement tool of FIG. 8 disposed within a drainage tube;

FIG. 10 shows a cross-sectional detail view of the drainage tube placement tool of FIG. 8 disposed within a drainage tube;

FIG. 11 shows a side view of a drainage tube placement tool according to another embodiment of the present disclosure;

FIG. 12 shows a side view of a cleaning device for a drainage tube according to an embodiment of the present disclosure;

FIG. 13 shows a top view of a surgical kit including a drainage device and a drainage tube placement tool according to an embodiment of the present disclosure; and

FIG. 14 shows a cross-sectional view of a drainage device according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

As used herein, the term “distal” relates to an end of a device configured to be inserted into the body cavity of a patient, and the term “proximal” relates to an end of a device configured to be outside of a patient.

In one embodiment of the present disclosure, a body cavity drainage device includes a body cavity drainage tube with a proximal end and a distal end. The proximal end of the body cavity drainage tube may be connected to an

activation apparatus including a rotatable control device and a compliant locking mechanism. Rotation of the rotatable control device may cause the distal end of the body cavity drainage tube to move relative to the proximal end of the drainage tube. In an unlocked position, the compliant locking mechanism may allow rotation of the rotatable control device. In a locked position, the compliant locking mechanism may substantially prevent rotation of the rotatable control device until a predetermined torque value is applied to the rotatable control device.

In another embodiment of the present disclosure, a body cavity drainage device includes a body cavity drainage tube extending along a central axis between a proximal end and a distal end. A fluid outlet may be oriented substantially coaxially with the drainage tube. The proximal end of the body cavity drainage tube may be attached to an activation apparatus. The activation apparatus may include a rotatable control device for controlling a position of the distal end of the body cavity drainage tube.

In yet another embodiment of the present disclosure, a body cavity drainage device placement tool for use with a body cavity drainage tube includes a shaft, a handle at or near a proximal end of the shaft, and a distal end of the shaft for insertion through at least one lateral opening of the body cavity drainage tube and at least partially through a central lumen of the body cavity drainage tube for placement of the distal end of the body cavity drainage tube in a body cavity of a patient.

In yet another embodiment of the present disclosure, a package including at least three of a body cavity drainage device, a drainage tube placement tool, a drainage tube cleaning device, and a visualization device may be provided to a user.

FIG. 1 shows a drainage device **100** according to an embodiment of the present disclosure. The drainage device **100** may include a drainage tube **102** configured to provide drainage to a body cavity defined by or surrounded by soft tissue. For example, the drainage device **100** may be used to withdraw infection exudates from a pleural cavity by applying suction to the drainage tube **102**. In addition, positive pressure may be applied to the drainage tube **102**, such as to introduce a fluid into the drainage tube **102** and/or body cavity, such as to dissolve material to be removed or to dislodge flow restrictions within the drainage tube **102**.

Although the drainage device **100** is described herein relative to use with pleural cavities, the present disclosure is not so limited. Accordingly, the drainage device **100**, elements thereof, and accompanying elements described in the present disclosure may be used for drainage from or introduction of fluids into other body cavities such as, by way of non-limiting example, veins, arteries, abdominal cavities, cranial cavities, etc.

The drainage tube **102** may include a proximal end **104** and a distal end **106**. The drainage tube **102** may include at least one of an axial opening **108** in the distal end **106** and one or more lateral openings **110** proximate the distal end **106** into an open lumen of the drainage tube **102**. The drainage device **100** may be configured to inhibit damage to the soft tissue surrounding the cavity while a portion of the drainage device **100** is inserted into the cavity or moved about within the cavity. For example, the distal end **106** of the drainage device **100** may include a substantially blunted geometry to prevent damage to the body cavity. In other words, the distal end **106** may not have any sharp, pointed, or abrupt edges that, if present, could puncture or otherwise damage soft tissue of a body cavity. In some embodiments, the drainage device **100** may include any and all of the

features and characteristics of the drainage devices described in U.S. patent application Ser. No. 13/840,986, filed Mar. 15, 2013 and published as US 2013/0211385, now U.S. Pat. No. 8,940,713, issued Jan. 27, 2015, which is incorporated herein by reference for all that it discloses.

In some embodiments, the axial opening **108** and the one or more lateral openings **110** may have an average diameter that is substantially the same size or smaller than an average inside diameter of the drainage tube **102**. Sizing the axial opening **108** and the one or more lateral openings **110** in this manner relative to the inside diameter of the drainage tube **102** may ensure that any clots (e.g., blood clots) suctioned into the drainage tube **102** are sufficiently small to pass through the drainage tube **102** without obstructing (e.g., clogging) the drainage tube **102**.

The proximal end **104** of the drainage tube **102** may be coupled to an activation apparatus **112** that may include a control device **114**. The control device **114** may be, for example, a knob configured to be manually manipulated (e.g., rotated) by a user, such as a practitioner, physician, nurse, patient, or care provider.

FIG. 2 shows a side view of the drainage device **100** of FIG. 1. The drainage device **100** may include an fluid outlet **202** in fluid communication with the drainage tube **102** and may be configured for connection to a vacuum source for removal of material from a body cavity or to a source of one or more treatments to be introduced into the body cavity. In some embodiments, the fluid outlet **202** may be an integral extension of the drainage tube **102**.

FIG. 3 shows a cross-sectional view of the drainage device **100** of FIG. 1. An activation apparatus **112** may be attached at or near the proximal end **104** of the drainage tube **102**. The activation apparatus **112** may include a pinion gear **302**, a first rack **304**, and a second rack **306**. The first and second racks **304**, **306** may be complementary to and meshed with the pinion gear **302**. First and second flexible members **308**, **310** may be attached to the first and second racks **304** and **306**, respectively. The first and second flexible members **308**, **310** may have an elongate shape and may include, for example, metallic wires made from steel, titanium, nitinol, or other metals or alloys. Additionally or alternatively, the first and second flexible members **308**, **310** may include synthetic or natural fibers. As a further example, such wires or fibers may include a single strand or multiple strands of one or more materials bundled or woven together. The first and second flexible members **308**, **310** may be disposed within closed lumens within a wall **312** of the drainage tube **102**. The lumens through which the first and second flexible members **308**, **310** extend may not be in fluid communication with the open lumen defined by the drainage tube **102** or with an exterior of the drainage tube **102**. In some embodiments, the flexible members **308**, **310** may be completely laterally enclosed within the wall **312** of the drainage tube **102**. The lumens may be positioned within the wall of the drainage tube **102** such that each of the flexible members **308**, **310** is substantially directly opposite the other across a diameter of the drainage tube **102**.

FIG. 4 shows another cross-sectional view of the drainage device **100** of FIG. 1. The pinion gear **302** may rotate in response to an applied torque **402**. As a non-limiting example, the torque **402** may be applied by a user manually operating the control device **114** (FIG. 1), which may be connected to the pinion gear **302**. Other embodiments may include an automated system configured to operate the control device **114**. Rotation of the pinion gear **302** may cause generally linear movement of the first rack **304** in a first direction **404** and a corresponding generally linear

5

movement of the second rack **306** in a second, opposite direction **406**. Movement of the first rack **304** may create tension in the first flexible member **308**, which imparts a compressive force to a first side **408** of the drainage tube **102**. Movement of the second rack **306** may allow slack in the second flexible member **310**. The compressive force from the first flexible member **308** may cause the drainage tube **102** to contract along the first side **408** in which the first flexible member **308** is disposed and lengthen along a second side **410** in which the second flexible member **310** is disposed, causing the drainage tube **102** to assume an arcuate (e.g., bent) shape, such as the shape shown in FIG. 4. The magnitude of the applied torque **402** and the corresponding refraction of the first flexible member **308** may determine the extent of curvature imparted to the drainage tube **102**. Torque may be applied in a direction opposite the direction indicated in FIG. 4, resulting in curvature of the drainage tube **102** in an opposite direction to the curvature shown. In some embodiments, the drainage device **100** may be configured such that the distal end **106** may rotate at least about 360° from a first fully curved position (e.g., pointing down and to the left in the perspective shown in FIG. 4) to a second, opposite fully curved position (e.g., pointing down and to the right from the same perspective).

In some embodiments, the drainage device **100** may include one or more optical fibers extending through lumens formed in the wall **312** of the drainage tube **102** and terminating at or near the distal end **106**. Such optical fibers may be connected to a visualization device (e.g., a camera providing an image to an electronic display) to assist a user in placing or moving the drainage tube **102** within a patient's body cavity.

Referring now to FIG. 5, the activation apparatus **112** may include a compliant locking mechanism **500**. The compliant locking mechanism **500** may have a locked position in which the compliant locking mechanism **500** maintains the control device **114** in a predetermined position selected by a user. The user may release (e.g., place the compliant locking mechanism **500** in an unlocked position) the compliant locking mechanism **500** to facilitate rotation of the control device **114**. In some embodiments, the compliant locking mechanism **500** may be configured to allow rotation of the control device **114** under a sufficiently high applied torque **402** (FIG. 4) even when the compliant locking mechanism is in the locked position.

In some embodiments, the compliant locking mechanism **500** may include a lock lever **502** with a proximal end **504** pivotably affixed to a main housing portion **506** of the activation apparatus **112**. As shown in FIG. 5, the proximal end **504** of the lock lever **502** may be resiliently (e.g., elastically) attached to the main housing portion **506**. In some embodiments, the lock lever **502** may be integrally molded with the main housing portion **506** (e.g., by an injection molding process). In other words, the lock lever **502** may include a flexible structural portion (i.e., the resilient attachment of the proximal end **504** to the main housing portion **506**) for rotating the lock lever **502** between the locked and unlocked positions. In other embodiments, the lock lever **502** may be attached to the main housing portion **506** with, e.g., a pinned hinge, and may be biased to a locked position by an elastic biasing element (e.g., a spring).

A distal end **508** of the lock lever **502** may include serrations (e.g., gear teeth) **510** configured to substantially mesh with gear teeth **512** of the pinion gear **302**. In a locked position, the serrations **510** of the distal end **508** of the lock lever **502** may mesh with the gear teeth **512** of the pinion

6

gear **302** and inhibit rotation of the pinion gear **302** when a torque is not applied (or an insufficient torque is applied) to the control device **114**, thereby fixing the control device **114** at a desired position.

When a user desires to unlock the compliant locking mechanism **500**, the user may depress the lock lever **502** with a force **602**, as shown in FIG. 6. The lock lever **502** may pivot at the proximal end **504**, and the serrations **510** (FIG. 5) of the distal end **508** may move downward (with reference to the orientation of FIG. 6) to clear (i.e., disengage from) the gear teeth **512** of the pinion gear **302** and facilitate rotation of the control device **114** and pinion gear **302**. The user may then rotate the control device **114** to the desired position and release the lock lever **502** to maintain the control device **114** in the selected position.

Alternatively, the user may leave the lock lever **502** in the locked position, and apply torque to the control device **114**. At a sufficiently high torque value, the lock lever **502** may elastically deform at one or more locations, e.g., at an angled juncture **604**. As torque is applied to the control device **114**, mechanical interaction between the serrations **510** (FIG. 5) and the gear teeth **512** may force the distal end **508** of the lock lever **502** in direction **606**, i.e., away from the pinion gear **302**. Under a sufficiently high applied torque, the lock lever **502** may elastically deform enough to enable the serrations **510** (FIG. 5) to disengage from the gear teeth **512** of the pinion gear **302** and allow rotation of the pinion gear **302** even when the lock lever **502** remains in a locked position (i.e., in the absence of force **602**). Thus, the compliant lock mechanism **500** may enable a user to adjust the position of the control device **114** without depressing the lock lever **502**, while maintaining the position of the control device **114** in the absence of a sufficiently high applied torque.

For example, the compliant lock mechanism **500** may be configured such that it avoids or reduces movement of the control device **114** resulting from incidental contact when in the locked position, but allows movement at a threshold level of applied torque. Such a level of applied torque may be, by way of example and not limitation, a torque value of greater than about 0.5 lb·ft (0.68 N·m), greater than about 1.0 lb·ft (1.36 N·m), or greater than about 5.0 lb·ft (6.8 N·m).

Accordingly, a method of draining fluid from a body cavity may include positioning a distal end of a tube of a body cavity drainage device at a first position within the body cavity. Fluid may be drained from the body cavity through the distal end of the tube of the body cavity drainage device while the distal end of the tube is in the first position. A user may depress a locking lever to unlock a rotatable control device of the body cavity drainage device external to the body cavity. The user may move the distal end of the tube of the body cavity drainage device to a second, different position within the body cavity. Moving the distal end of the tube of the body cavity drainage device may include rotating the rotatable control device of the body cavity drainage device, and the rotatable control device may be coupled to the distal end of the tube of the body cavity drainage device by flexible members.

In some embodiments, a drainage device may include a fluid outlet that is substantially aligned with the drainage tube. For example, referring now to FIG. 7, a schematic side view of another embodiment of a drainage device **700** is shown. In this embodiment, a drainage tube **702** extends along a central axis A_c , through an activation apparatus **704**, and to a fluid outlet **706** also aligned along the central axis A_c . In some embodiments, a single tube extending through the activation apparatus **704** may form the drainage tube **702**

and the fluid outlet **706**. In other words, the drainage device **700** may comprise a unitary drainage tube **702** with a distal end **708** for insertion into a body cavity of a patient, a proximal end **710** including a fluid outlet **706**, and an activation apparatus **704** disposed on the drainage tube **702** between the proximal end **710** and the distal end **708**. In other embodiments, the drainage tube **702** and the fluid outlet **706** may be two separate tubes coupled (e.g., bonded, press-fit, glued) together.

In the embodiment of FIG. 7, a control device **714** may be disposed in a position offset from a central axis A_c of the drainage tube **702**. At least one flexible member **718**, substantially as described above in connection with FIGS. 3 and 4, may extend from the control device **714** along an at least partially curvilinear (i.e., arcuate) path **720**. The at least one flexible member **718** may be constrained to the curvilinear path **720** by guides **716** in the activation apparatus **704** and channels in the drainage tube **702**. The control device **714**, the at least one flexible member **718**, and the drainage tube **702** may function in a similar manner to that described above in connection with FIGS. 3 and 4. The activation apparatus **704** may further include a compliant locking mechanism, as described above in connection with FIGS. 5 and 6.

Referring now to FIG. 8, a side view of a drainage tube placement tool **800** is shown. The drainage tube placement tool **800** may include a handle **802** affixed to a shaft **804** at a proximal end **806**. The shaft **804** may be substantially straight, or may include a curved portion **810** near a distal end **808**, as shown in FIG. 8. In some embodiments, the shaft **804** may have a substantially circular cross-sectional shape. In other embodiments, the shaft **804** may have a different cross-sectional shape, such as an elliptical shape, a rectangular shape, or combinations thereof.

The shaft **804** may include a shoulder **812** (e.g., a step) where the cross-sectional shape of the shaft **804** varies from a first diameter **814** to a second, smaller diameter **816**. As shown in FIG. 8, the shoulder **812** may be disposed proximate the distal end **808** of the shaft **804**. By way of example and not limitation, the shoulder **812** may be positioned within about one (1) inch (25.4 mm) or less of the distal end **808** of the shaft **804**. In other embodiments (e.g., as shown below in FIG. 10), the shoulder may be disposed proximate the handle portion **802**, or the drainage tube placement tool **800** may not include a shoulder.

Referring now to FIG. 9, a user may insert the shaft **804** of the drainage tube placement tool **800** through a lateral opening **910** of a drainage tube **902**. The lateral opening **910** may be similar to the lateral openings **110** described in connection with FIGS. 1 and 2. In some embodiments, the lateral opening **910** may include features configured to facilitate insertion of the drainage tube placement tool **800** within the drainage tube **902**. For example, a slit **912** may extend from a periphery of the lateral opening **910** into a wall **914** of the drainage tube **902**. Upon insertion of the distal end **812** (FIG. 8) of the drainage tube placement tool **800** within the lateral opening **910**, the slit **912** may at least partially open, as shown in FIG. 9, to ease passage of the drainage tube placement tool **800** through the drainage tube **902**. Upon removal of the drainage tube placement tool **800** from the drainage tube **902**, the slit **912** may substantially close, and the diameter of the lateral opening **910** may be substantially similar to the diameter of other lateral openings **916**. Suction applied to the drainage tube **902** after removal of the drainage tube placement tool **800** may also assist the

slit **912** to close. In other embodiments, the diameter of the lateral opening **910** may be greater than the diameter of other lateral openings **110**.

The drainage tube placement tool **800** may be configured to stop at a predetermined insertion distance within the drainage tube **902**. Referring now to FIG. 10, after the drainage tube placement tool **800** (FIG. 8) is inserted into the lateral opening **910** (FIG. 9) of the drainage tube **902**, the user may continue to insert the drainage tube placement tool **800** within the drainage tube **902** until the shoulder **812** of the shaft **804** of the drainage tube placement tool **800** abuts a ferrule **1000** disposed near the distal end **1004** of the drainage tube **902** and the shoulder **812** prevents further insertion of the placement tool **800** within the drainage tube **902**. The portion of the shaft **804** having the second diameter **816** (FIG. 8) may enter an axial opening **1002** of the ferrule **1000**. In this position, the distal end **808** (FIG. 8) of the drainage tube placement tool **800** may be disposed proximate the distal end **1004** of the drainage tube **902**. In some embodiments, the axial opening **1002** of the ferrule **1000** may have a diameter smaller than an inside diameter of the drainage tube **902**.

In some embodiments, the shaft **804** of the drainage tube placement tool **800** may have a length sufficient to extend through the lateral opening **910** of the body cavity drainage tube **902**, through a central lumen of the body cavity drainage tube **902**, and position the distal end **808** of the shaft **804** past the distal end **1004** of the drainage tube **902**. In other words, when the shaft **804** is inserted fully into the body cavity drainage tube **902**, the distal end **808** of the shaft **804** may protrude beyond the distal end **1004** of the drainage tube **902**.

In some embodiments, at least one of the flexible members **308**, **310** (FIG. 3) or **718** (FIG. 7) may be attached to the ferrule **1000**. In other words, the ferrule **1000** may be coupled to a control device (e.g., control device **114** (FIGS. 1 and 2) or control device **714** (FIG. 7)) of an activation apparatus (e.g., activation apparatus **112** (FIG. 3) or activation apparatus **704** (FIG. 7)) through one or more flexible members **308**, **310**, and **718**.

The drainage tube placement tool **800** may contribute additional stiffness (i.e., rigidity) to the drainage tube **902** to enable a user to insert the drainage tube **902** through an incision in a patient's body and into, e.g., the pleural cavity, without collapsing (e.g., kinking) the drainage tube **902**. In some embodiments, the drainage tube placement tool **800** may be made from a material having a greater modulus of elasticity (i.e., a greater stiffness) than the material of the drainage tube **902**.

In use, a user may insert the distal end **808** of the drainage tube placement tool **800** into the drainage tube **902**, grasp the handle **802**, and insert the drainage tube **902** with the drainage tube placement tool **800** disposed therein through an incision and into the body cavity. The user may then remove the drainage tube placement tool **800** from the drainage tube **902**, leaving at least a portion of the drainage tube **902** disposed within the body cavity.

The curved portion **810** of the drainage tube placement tool **800** may be shaped to ease insertion of the drainage tube **902** with the drainage tube placement tool **800** disposed therein within a body cavity of a particular configuration. For example, the curved portion **810** of the drainage tube placement tool **800** may have a shape of a desired path the drainage tube **902** may follow as the drainage tube **902** is inserted into a body cavity. By way of another example, the curve may facilitate directing the placement of the drainage tube **902** within the body cavity.

Referring now to FIG. 11, another embodiment of a drainage tube placement tool 1100 is shown. The drainage tube placement tool 1100 may include a shaft 1104 with a shoulder 1102 disposed near a proximal end 1106 of the shaft 1104. A distal end 1108 of the shaft 1104 may be inserted in a lateral opening 910, 916 (FIG. 9) of a drainage tube 902. The shoulder 1102 may abut a wall 914 (FIG. 9) of the drainage tube 902 surrounding the lateral opening 910, 916 at a predetermined insertion distance. In other embodiments, the shoulder 1102 may be absent, and a handle 1110 may abut against the lateral opening 910, 916 to stop further insertion of the drainage tube placement tool 1100 into a drainage tube. Thus, the drainage tube placement tool 1100 may be used with a drainage tube device that does or does not include a ferrule 1000 (FIG. 10). For example, the drainage tube placement tool 1100 may be used with a drainage device according to the present disclosure, e.g., drainage devices 100, 700, or may be used with prior art drainage devices. As shown in FIG. 11, the shaft 1104 of the drainage tube placement tool 1100 may be substantially straight. In other embodiments, the shaft 1104 of the drainage tube placement tool 1100 may include a curved portion 810 like that shown in the embodiment of FIG. 8.

In some embodiments, the shaft 804, 1104 of the drainage tube placement tool 800, 1100 may be hollow (e.g., may include a channel therethrough) to accommodate a guide wire for aiding placement of the drainage tube within a body cavity and/or to accommodate one or more optical fibers therein. A guide wire may be placed in a desired location through a hollow needle, and one or more dilators may be threaded over the guide wire to expand an incision made by the hollow needle through the skin and/or other tissue. When the incision is sufficiently expanded, the drainage tube placement tool 800, 1100 may be inserted into a drainage tube 102, 702 as described above, and the guide wire may be threaded through the drainage tube placement tool 800, 1100. A distal end of the drainage tube 102, 702 may then be placed in the body cavity through the expanded incision using the guide wire. In some embodiments, one or more optical fibers may be inserted through the channel of the drainage tube placement tool 800, 1100. The one or more optical fibers may be connected to a visualization device (e.g., a camera in communication with an electronic display) to assist the user in placing a drainage tube 102, 702 within the body cavity.

FIG. 12 shows an embodiment of a cleaning device 1200 according to the present disclosure. The cleaning device 1200 may include a handle 1202, a shaft 1204, and a cleaning instrument 1206. The cleaning instrument 1206 may be configured to be inserted through an fluid outlet 202, 704 (FIGS. 2 and 7) of the drainage device 100, 700. In some embodiments, the cleaning instrument 1206 may be inserted into the drainage device 100, 700 while a portion of the drainage tube 102 remains disposed within a body cavity. The cleaning instrument 1206 may be configured to retrieve solid matter, e.g., blood clots or other coagulations of physiological fluids, from the drainage tube 102. In use, a user may remove a vacuum source from the fluid outlet 202, 704 of the drainage device 100, 700. The user may then insert the cleaning instrument 1206 into the fluid outlet 202, 704, grasp the handle 1202, and feed the cleaning device 1200 into the drainage tube 102 until the cleaning instrument 1206 contacts the solid matter. The user may remove the cleaning device 1200 and solid matter from the drainage tube 102 and reconnect the vacuum source to the fluid outlet 202, 704. In some embodiments, the cleaning instrument 1206 may comprise a coil of resilient material, such as a

metal alloy or a polymer. The cleaning instrument 1206 may have a helical shape, which may be rotated within the drainage tube 102 to force the solid matter out of the drainage tube 102.

Referring to FIG. 13, a surgical kit 1300 may include at least a drainage device 100, 700 and a drainage tube placement tool 800, 1100. Each of the drainage device 100, 700 and the drainage tube placement tool 800, 1100 in the surgical kit 1300 may be substantially as described above. In some embodiments, the surgical kit 1300 may also include one or more of a cleaning device 1200 for removal of obstructions in the drainage device 100, 700, a guide wire to facilitate placement of the drainage device 100, 700, at least one dilator for expanding an incision to facilitate placement of the drainage device 100, 700, and a visualization device 1302 to facilitate placement of the drainage device 100, 700. The visualization device 1302 may include, for example, a fiber optic scope and/or a camera. The elements in the surgical kit 1300 may provide complementary tools for a surgeon or other practitioner to use for draining a patient's body cavity. Each of the elements in the surgical kit 1300 or portions thereof may be sterilized and otherwise prepared for use in surgery. In addition, one or more of the elements in the surgical kit 1300 may be provided at least partially within a sterile envelope, protective covering, enclosure, or other container within the surgical kit 1300 for additional protection from contamination or damage.

FIG. 14 illustrates an embodiment of a drainage device 1400 including an activation apparatus 1412 and a detachable drainage tube 1402. The activation apparatus 1412 and detachable drainage tube 1402 may be configured to be detachably coupled together for positioning the detachable drainage tube 1402 in a body cavity (e.g., for initial insertion and/or for repositioning within the body cavity). The activation apparatus 1412 and detachable drainage tube 1402 may be selectively detached from each other, such as to provide increased mobility to a patient. The detachable drainage tube 1402 may include at least some similar features as the drainage tube 102 described above. For example, the detachable drainage tube 1402 may include a proximal end 1404, a distal end 1406, and one or more lateral openings 1410 proximate the distal end 1406 of the detachable drainage tube 1402. The detachable drainage tube 1402 may also include elongated flexible members 1408 extending from the proximal end 1404 to at or near the distal end 1406 of the detachable drainage tube 1402, which may be disposed within lumens longitudinally extending through a sidewall of the detachable drainage tube 1402.

The activation apparatus 1412 may include at least some similar features as the activation apparatus 112 described above. For example, the activation apparatus 1412 may include a control device 1414, such as a knob or other element configured to be manually manipulated (e.g., rotated) by a user to remotely move the distal end 1406 of the detachable drainage tube 1402 when coupled thereto. The control device 1414 may include a pinion configured to engage with first and second racks 1416, 1418.

The proximal end 1404 of the detachable drainage tube 1402 may be configured to couple the detachable drainage tube 1402 to the activation apparatus 1412, and the activation apparatus 1412 may be configured to couple with the detachable drainage tube 1402 in a complementary fashion. Additionally, a linking element 1420 may be coupled to a proximal end of each of the elongated flexible members 1408 for operably connecting each of the elongated flexible members 1408 to a respective one of the first and second racks 1416, 1418. By way of example and not limitation,

11

each linking element **1420** may include a hook and each of the first and second racks **1416**, **1418** may include a complementary slot or hook **1421**. When operably connected, the hook of the linking element **1420** may latch onto the complementary slot or hook **1421** of the respective one of the first and second racks **1416**, **1418**. By way of another example, the linking element **1420** may include a notch (e.g., an annular notch) and each of the first and second racks **1416**, **1418** may include a complementary ridge or O-ring configured to deflect and snap into the notch of the linking element **1420** when the detachable drainage tube **1402** is operably connected to the activation apparatus **1412**.

The activation apparatus **1412** may include a suction tube **1422** that may be configured to form a fluid seal with a proximal end of the detachable drainage tube **1402** when the detachable drainage tube **1402** is operably connected to the activation apparatus **1412**. Accordingly, suction may be applied to the suction tube **1422** to draw fluids from a body cavity through the detachable drainage tube **1402**.

Accordingly, the drainage device **1400** may be used to withdraw fluids from a body cavity of a patient by inserting the distal end **1406** of the detachable drainage tube **1402** into the body cavity and, prior to or after insertion of the distal end **1406** of the detachable drainage tube **1402**, operably coupling the activation apparatus **1412** to the proximal end **1404** of the detachable drainage tube **1402**. To operably couple the activation apparatus **1412** to the detachable drainage tube **1402**, a fluid seal may be formed between the detachable drainage tube **1402** and the suction tube **1422** and the linking elements **1420** may be coupled to the first and second racks **1416**, **1418**. When operably connected, the activation apparatus **1412** may be used to remotely position the distal end **1406** of the detachable drainage tube **1402** within the body cavity.

The activation apparatus **1412** may also be detached from the detachable drainage tube **1402**, such as to enable increased patient mobility. For example, the linking elements **1420** may be decoupled from the first and second racks **1416**, **1418**, and the detachable drainage tube **1402** may be decoupled from the suction tube **1422**. In some embodiments, after the activation apparatus **1412** is detached from the detachable drainage tube **1402**, the proximal end of the detachable drainage tube **1402** may be capped or plugged to inhibit fluid from inadvertently draining out of the detachable drainage tube **1402**.

Referring to FIG. **14** in conjunction with FIG. **13**, the surgical kit **1300** may, in some embodiments, include the drainage device **1400** in a detached or an attached configuration. In some embodiments, more than one detachable drainage tube **1402**, such as identical detachable drainage tubes **1402** or detachable drainage tubes **1402** of different lengths, diameters, materials, stiffnesses, etc., may be included in the surgical kit **1300**.

While the disclosure may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the disclosure is not intended to be limited to the particular forms disclosed. Additionally, embodiments and features of the disclosure shown and/or described separately may be combined.

What is claimed is:

1. A body cavity drainage device for a patient, comprising:

a drainage tube having a proximal end, a distal end, and one or more lumens extending longitudinally through a wall thereof, the distal end configured to be inserted

12

into a body cavity of a patient to facilitate use of the body cavity drainage device; and

an activation apparatus configured to alter a position of the distal end of the drainage tube relative to the proximal end of the drainage tube, the activation apparatus comprising:

a housing portion;

a rotatable control device rotatably coupled to the housing portion;

one or more elongated flexible members disposed within the one or more lumens extending longitudinally through a wall of the drainage tube, the one or more flexible members operably coupled to the rotatable control device at a proximal end of the one or more flexible members and to the drainage tube at or near a distal end of the one or more flexible members; and

a compliant locking mechanism configured to maintain an angular position of the rotatable control device when in a locked position and in the absence of a torque applied to the rotatable control device, and to allow rotation of the control device when in an unlocked position upon application of a torque to the rotatable control device, the compliant locking mechanism comprising:

a locking lever having a distal end configured to engage with the rotatable control device in the locked position, and having a proximal end resiliently attached to the housing portion for rotating between the locked position and the unlocked position, wherein the distal end of the locking lever has a concave profile matching a convex profile of the rotatable control device.

2. The body cavity drainage device of claim 1, wherein the compliant locking mechanism is configured to allow rotation of the control device when in the locked position upon application of torque of a predetermined value to the control device.

3. The body cavity drainage device of claim 2, wherein the torque of a predetermined value is a torque of at least about 1 lb·ft (1.36 N·m).

4. The body cavity drainage device of claim 1, wherein the proximal end of the locking lever is integrally molded with the housing portion.

5. The body cavity drainage device of claim 1, wherein the locking lever is biased to the locked position.

6. The body cavity drainage device of claim 1, wherein the locking lever comprises a flexible structural portion configured to be manually depressed by a user.

7. The body cavity drainage device of claim 1, wherein the locking lever is configured to move from the locked position to the unlocked position upon being manually depressed.

8. The body cavity drainage device of claim 1, wherein the distal end of the locking lever comprises serrations.

9. The body cavity drainage device of claim 8, wherein the control device comprises a pinion gear, and wherein the serrations of the locking lever are configured to engage with gear teeth of the pinion gear when the compliant locking mechanism is in the locked position.

10. The body cavity drainage device of claim 9, wherein the serrations of the locking lever are configured to disengage from the gear teeth of the pinion gear when the locking lever is in the unlocked position.

11. The body cavity drainage device of claim 8, wherein the locking lever comprises a compliant portion proximate the distal end of the locking lever.

13

12. The body cavity drainage device of claim 11, wherein the compliant portion comprises an angled juncture between two portions of the locking lever.

13. A body cavity drainage device for a patient, comprising:

a drainage tube having a proximal end and a distal end; and

an activation apparatus coupled to the proximal end of the drainage tube, the activation apparatus comprising:

a pinion gear attached to a control device;

at least one rack configured to mesh with the pinion gear;

at least one flexible member extending along a length of the drainage tube and coupled to the distal end of the drainage tube, the at least one flexible member attached to the at least one rack; and

a compliant locking mechanism proximate the control device, the compliant locking mechanism comprising a resilient locking lever configured to resiliently rotate between a locked position and an unlocked position and serrations configured to engage with gear teeth of the pinion gear when the locking lever is in the locked position, wherein the locking lever is located outside of a profile of the pinion gear.

14. The body cavity drainage device of claim 13, wherein the at least one rack configured to mesh with the pinion gear comprises two racks configured to mesh with the pinion gear, and wherein the at least one flexible member comprises two flexible members, each of the two flexible members attached to a respective rack of the two racks.

15. The body cavity drainage device of claim 13, wherein the serrations of the compliant locking mechanism are configured to disengage from the gear teeth of the pinion gear upon application of a torque of at least a predetermined value to the control device.

16. A method of forming a body cavity drainage device for a patient, comprising:

coupling an activation apparatus to a proximal end of a drainage tube, the activation apparatus configured to bend the drainage tube in response to a torque input at a rotatable control device of the activation apparatus;

forming a locking mechanism by resiliently coupling a proximal end of a locking lever to a housing of the activation apparatus; and

14

engaging a concave distal end of the locking lever with a convex outer profile of the rotatable control device to substantially prevent rotation of the rotatable control device in the absence of an applied torque to the rotatable control device.

17. The method of claim 16, wherein resiliently coupling a proximal end of a locking lever to a housing of the activation apparatus comprises providing clearance sufficient to enable the locking lever to resiliently move between an unlocked position and a locked position in which free rotation of the control device is allowed.

18. The method of claim 16, wherein engaging a distal end of the locking lever with the rotatable control device comprises compliantly engaging the distal end of the locking lever with the rotatable control device to allow rotation of the rotatable control device when the locking mechanism is in a locked position and torque of a predetermined value is applied to the rotatable control device.

19. A method of draining fluid from a body cavity, comprising:

positioning a distal end of a tube of a body cavity drainage device at a first position within the body cavity;

engaging a concave distal end of a locking lever resiliently coupled to a housing of an activation apparatus at a proximal end of the locking lever with an outer surface of a rotatable control device of the body cavity drainage device external to the body cavity to lock the rotatable control device in position;

draining fluid from the body cavity through the distal end of the tube of the body cavity drainage device in the first position;

depressing the locking lever to rotate the concave distal end of the locking lever away from engagement with the rotatable control device of the body cavity drainage device to unlock the rotatable control device; and

moving the distal end of the tube of the body cavity drainage device to a second, different position within the body cavity, comprising:

rotating the rotatable control device of the body cavity drainage device, the rotatable control device being coupled to the distal end of the tube of the body cavity drainage device by flexible members.

* * * * *